

DEVIL S3



Standard EN ISO 20345 : 2011



LEMAITRE

Safety since 1974

www.perezperez.es



PRODUCT HIGHLIGHT

0% metal model. Suitable for areas equipped with metal detectors (warehouses,...).

Sizes 35 to 48

Ref. DEVIS30NR

Product Highlights



■ **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.



■ **3D Microporous fabric lining, soft and breathable** pleasant feel of freshness, great ventilation of the foot.

■ **Anti-abrasion vamp and heel**, additional resistance of the upper that ensures a long life span.

■ **Tongue with gusset** to limit intrusion of dust and stones.



■ **Protective toe-cap:** polycarbonate.



■ **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



C07 PU nitrile

■ **Wide and comfortable shoe**

■ **Versatility:** effective spikes on industrial floors and outdoor surfaces

■ **Extended contact area and 10 mm offset heel:** self-cleaning and multi-functional sole with excellent stability

■ **Sole resistant up to a temperature of 300°** (HRO standard), contact heat resistance.

■ **Excellent abrasion resistance.**

■ **Rounded heel attack** for a natural rolling of the foot

USAGE

■ Indoor and outdoor use: excellent versatility.



FRENCH
TRADEMARK

lemaitre-securite.com

Lemaitres takes care.



VARIANT

DEVIL S3



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent leather with reinforced anti-abrasion vamp and heel
- **Tongue with gusset:** water-repellent leather
- **Lining:** 3D microporous fabric

Characteristics of the sole

- **Designation:** C07
- **Material:** polyuréthane / nitrile
- **Antistatic sole**
- **Coefficient d'adhérence SRA :**
forward flat slip: 0,33 (norme ≥ 0,32)
forward heel slip: 0,31 (norme ≥ 0,28)
- **Coefficient d'adhérence SRB :**
forward flat slip: 0,18 (norme ≥ 0,18)
forward heel slip: 0,14 (norme ≥ 0,13)



Devon S3 SRC
DEVOS30NR

Practical information

Weight of one shoe size p.42: 699 g

AET N°OZO299-CPT006/22

Packaging

Sizes 35 to 42

boîte 315 x 220 x 125 mm

carton 635 x 445 x 325 mm

10 shoeboxes per carton

Sizes 43 to 48

boîte 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

35 3237154486351 **43** 3237154486436

36 3237154486368 **44** 3237154486443

37 3237154486375 **45** 3237154486450

38 3237154486382 **46** 3237154486467

39 3237154486399 **47** 3237154486474

40 3237154486405 **48** 3237154486481

41 3237154486412

42 3237154486429

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Shock absorption at the heel



Fuel oil-resistant outsole



Water penetration and water absorption resistant upper



Electrostatic discharge



Insulation against cold



Insulation against heat



Outsole resistance to hot contact



Water resistant



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



Slip-resistance on ceramic floors with detergent and steel floors with glycerol

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE

Safety since 1974

Member of
SYNAMAP



DON_LS 04 TDS 0120
updated : 22/12/22