

SUPERVRAC TAN



BULK MATERIALS HANDLING

Bulk tank truck discharge



APPLICATIONS

Pneumatic transport of bulk abrasive products.

Discharge from road and rail tankers, and delivery to storage bins: cement, sand, lime and also cereals, fertilizers, cattle feed and chemicals (PVC, dye stuffs, granulates, etc.).

ADVANTAGES

- ¹ Light weight, flexible hose that coils flat.
- ¹ Excellent resistance to abrasion.

TECHNICAL DESCRIPTION

Inner tube: heavy duty abrasion resistant NR, beige, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30°C to +70°C.

Electrical properties: non conductive tube with built-in wire.

**BULK MATERIALS HANDLING****SUPERVRAC TAN**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
75.0	6 ±1.25	87.0 ±1.5	7	21	1.72	20	0070661	120
75.0	6 ±1.25	87.0 ±1.5	7	21	1.72	40	0125111	120
89.0	6 ±1.25	101.0 ±1.5	7	21	1.98	20	0060614	1
89.0	6 ±1.25	101.0 ±1.5	7	21	1.98	40	0060615	1
100.0	6 ±1.25	112.0 ±1.2	7	21	2.24	20	0070664	120
100.0	6 ±1.25	112.0 ±1.2	7	21	2.24	40	0070665	120
110.0	6.5 ±1.25	123.0 ±1.5	7	21	2.5	20	0060617	120
110.0	6.5 ±1.25	123.0 ±1.5	7	21	2.5	40	0060618	120

Tolerance on length: ±1% (ISO 1307 Standard).



www.perezypererez.es

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING