

FABIO S3



STANDARD EN ISO 20345 : 2011



LEMAITRE


Safety since 1974

www.perezperez.es



CARBON




by LEMAITRE



Carbon fiber toe-cap
Cutting-edge technology from
the aeronautical industry

Sizes 35 to 49 Ref. FABIS30BE

Product Highlights

-  **Carbon toe-cap by Lemaître:** ergonomic build, lightness, similar resistance to steel, athermic and non-magnetic
- Memory Foam insole by Lemaître:** antibacterial memory structure, odor neutralizer, MSDs prevention
- Microfiber upper and retro-reflective side marker:** enhanced visibility. Lightness, breathability and resistance to tearing and abrasion
- Bellows tongue:** to limit intrusion of dust and stones, reinforced abrasion-resistant cap, increased resistance
- Reinforced abrasion-resistant cap,** increased resistance
-  **Protective toecap:** Carbon by Lemaître
-  **Puncture resistant midsole:** high tenacity fabric «0» penetration



Anti-static sole CARBON PU2D

- Developed outsole for industrial and urban floors**
- Large bearing surface:** optimal stability
- Shock absorption:** preservation of the back and joints
- Conformal to bent positions:** knee notches and crouching
- Sculpted studs:** reinforced grip

USE

- Finishing works, light industry, logistics, services, handling



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



FABIO S3



STANDARD EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent microfiber with an abrasion-resistant cap in «groove»
- **Bellows tongue:** abrasion-resistant textile
- **Collar:** abrasion-resistant textile
- **Lining:** 3D microporous fabric

Characteristics of the sole

- **Designation:** CARBON PU2D
- **Material:** polyuréthane / polyuréthane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,34 (standard ≥ 0,32)
forward heel slip: 0,31 (standard ≥ 0,28)
- **Coefficient d'adhérence SRB :**
forward flat slip: 0,22 (standard ≥ 0,18)
forward heel slip: 0,20 (standard ≥ 0,13)

VARIANT



Flavio S3 SRC
FLAVS30BE

Practical information

Weight of one shoe size.42 : 530 g

AET N° 0075/007/161/09/19/2718 EXT 12/03/20

Packaging

Sizes 35 to 42

shoebox 315 x 220 x 123 mm

carton 635 x 445 x 315 mm

10 shoeboxes per carton

Sizes 43 to 49

shoebox 355 x 220 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

35	3237154303351	43	3237154303436
36	3237154303368	44	3237154303443
37	3237154303375	45	3237154303450
38	3237154303382	46	3237154303467
39	3237154303399	47	3237154303474
40	3237154303405	48	3237154303481
41	3237154303412	49	3237154303498
42	3237154303429		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200J toecap: protection of the forefoot against impact and crushing



Anti-perforation insert 1100 N: foot protection against perforation



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = SRA + SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE

Safety since 1974

DON_LS04TDS0021
Update : 10/03/20

Member of
SYNAMAP

