

# FLOYD S3 LOW



STANDARD EN ISO 20345 : 2011




[www.perezyperez.es](http://www.perezyperez.es)



**LEMAITRE**

*Safety since 1974*

**CARBON**  
by LEMAITRE



**Carbon fiber toe-cap**  
Cutting-edge technology from  
the aeronautical industry



**Sizes 35 to 49**

Reference code: **FLOY30NR**

## Product Highlights



- **Carbon toe-cap by Lemaitre** : ergonomic build, lightness, similar resistance to steel, athermic and non-magnetic

- **Memory Foam insole by Lemaitre**: anti-bacterial memory structure, odor neutralizer, MSDs prevention



- **1.7-1.8 mm thick leather** and retro-reflective side marker, enhanced visibility

- **Bellows Tongue**: to limit intrusion of dust and stones

- Reinforced abrasion-resistant cap, increased resistance



- **Protective toe-cap**: Carbon by Lemaitre



- **Puncture resistant midsole**: high tenacity fabric "0" penetration



## Anti-static sole CARBON PU2D

- **Developed outsole for industrial and urban floors**

- **Large bearing surface**: optimal stability

- **Shock absorption**: preservation of the back and joints

- **Conformal to bent positions**: knee notches and crouching

- **Sculpted studs**: reinforced grip

## USAGE

- Finishing works, light industry, logistics, services, handling



[lemaitre-securite.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority



# FLOYD S3 LOW



STANDARD EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material** : water-repellent microfiber with an abrasion-resistant cap in "groove"
- **Bellows tongue**: abrasion-resistant textile
- **Collar** : abrasion-resistant textile
- **Lining**: 3D microporous fabric

## Characteristics of the sole

- **Designation** : CARBON PU2D
- **Material** : polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient** :  
forward flat slip: 0,34 (standard  $\geq 0,32$ )  
forward heel slip: 0,31 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient** :  
forward flat slip: 0,22 (standard  $\geq 0,18$ )  
forward heel slip: 0,20 (standard  $\geq 0,13$ )

## VARIANT



**Felix S3 SRC**  
FELIS30NR

## Practical Information

Weight of one shoe size 42 : 540 g

**CERTIFICATION N°** 0075/007/161/09/19/2718 EXT 07/03/20

## Packaging

### sizes 35 to 42

**shoebbox** 315 x 220 x 123 mm

**carton** 635 x 445 x 315 mm

10 shoeboxes per carton

### sizes 43 to 49

**shoebbox** 355 x 220 x 130 mm

**carton** 660 x 450 x 360 mm

10 shoeboxes per carton

## Gencods

<b>35</b>	3237154284353	<b>43</b>	3237154284438
<b>36</b>	3237154284360	<b>44</b>	3237154284445
<b>37</b>	3237154284377	<b>45</b>	3237154284452
<b>38</b>	3237154284384	<b>46</b>	3237154284469
<b>39</b>	3237154284391	<b>47</b>	3237154284476
<b>40</b>	3237154284407	<b>48</b>	3237154284483
<b>41</b>	3237154284414	<b>49</b>	3237154284490
<b>42</b>	3237154284421		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

<b>SBP</b>			
<b>S1</b>			
<b>S1P</b>			
<b>S2</b>			
<b>S3</b>			

200 J toe-cap: protection of the forefoot against impact and crushing

Anti-perforation insert 1100 N: foot protection against perforation

<b>A</b>	Anti-static footwear	<b>Ci</b>	Insulation against cold
<b>E</b>	Shock absorption at the heel	<b>Hi</b>	Insulation against heat
<b>Fo</b>	Fuel oil-resistant outsole	<b>Hro</b>	Outsole resistance to hot contact
<b>Wru</b>	Water penetration and water absorption resistant upper	<b>Wr</b>	Water resistant
<b>ESD</b>	Electrostatic discharge	<b>An</b>	Ankle protection
<b>SRA</b>	Slip-resistance on ceramic floors with detergent		
<b>SRB</b>	Slip-resistance on steel floors with glycerol		
<b>SRC</b>	= <b>SRA</b> + <b>SRB</b>		

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

**lemaitre-securite.com**



Member of  
**SINAMAP**



**DON\_LS 04 TDS 0018**  
Update : 10/03/20