



# Dry-Break Couplings



[www.perezyperez.es](http://www.perezyperez.es)

## DRY-BREAK COUPLINGS

### CERTIFICATES/APPROVALS

- TÜ.AGG.162-93 (ADR, RID, IMDG and TA-Luft)
- European directives 97/23/EC (PED)
- 94/9/EC (ATEX) compliant
- EN ISO 9001:2008
- ISO 14001 certificate
- OHSAS 18001:2007

### FEATURES

- Extremely reliable and simple single action operation
- Safe transfer of hazardous or high value liquid products
- Minimal residual loss on disconnection
- Lock pin feature (2" to 4") standard
- In-built swivel adaptor for hose unit
- Easy servicing

### TECHNICAL DETAILS

- Materials: Stainless Steel 316L, other on request
- Seals: FKM (Viton®), other on request
- Working pressure: PN 25 (test pressure: PN 37.5)
- End connections: BSP threads, other on request
- Compatibility: NATO STANAG 3756

[www.trelleborg.com/fluidhandling](http://www.trelleborg.com/fluidhandling)

Contact: [tes.serviceclients@trelleborg.com](mailto:tes.serviceclients@trelleborg.com)

| HOSE UNIT |             |          |       |
|-----------|-------------|----------|-------|
| Sizes     | BSP threads | Code no. | Stock |
| 25        | 1"          | 5105392  | ✓     |
| 50        | 2"          | 5105393  | ✓     |
| 80        | 3"          | 5105394  | ✓     |
| 100       | 4"          | 5105395  | ✓     |



| TANK UNIT |             |          |       |
|-----------|-------------|----------|-------|
| Sizes     | BSP threads | Code no. | Stock |
| 25        | 1"          | 5105396  | ✓     |
| 50        | 2"          | 5105397  | ✓     |
| 80        | 3"          | 5105398  | ✓     |
| 100       | 4"          | 5105399  | ✓     |

